OVERVIEW



| 1. | USB-C (USB 10Gbps), with PD 140W & DP 1.4 | 6. HDMI |
|----|---|----------------------|
| 2. | E-shutter switch | 7. Ethernet (RJ-45) |
| 3. | Combo audio jack | 8. USB-A (USB 5Gbps) |
| 4. | USB-A (USB 5Gbps) | 9. Power connector |
| 5. | USB-A (USB 5Gbps) | |

Notes:

• Port 1: PD 140W is the input power and requires the use of Lenovo unique adapter, otherwise it may support lower than 140W.

PERFORMANCE

Processor

Processor Family

AMD Ryzen[™] 5 / 7 Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | |
|---------------------------------|-------|---------|----------------|---------------|------------------|--|
| AMD Ryzen [™] 5 7235HS | 4 | 8 | 3.2GHz | 4.2GHz | 2MB L2 / 8MB L3 | |
| AMD Ryzen™ 7 7435HS | 8 | 16 | 3.1GHz | 4.5GHz | 4MB L2 / 16MB L3 | |

Operating System

Operating System**

- Windows[®] 11 Pro
- Windows® 11 Home
- Windows[®] 11 Home Single Language
- No preload operating system

Graphics

Graphics**

| Graphics | Туре | Memory | Boost Clock | TGP | Key Features |
|--|----------|--------------|----------------|------|--|
| NVIDIA® GeForce RTX™ 3050 Laptop GPU | Discrete | 6GB GDDR6 | 1732 MHz | 95W | DLSS 2, Dynamic Boost 2.0, DirectX® 12 Ultimate |
| NVIDIA® GeForce RTX™ 3050A Laptop GPU | Discrete | 4GB GDDR6 | 2205 MHz | 65W | DLSS, Dynamic Boost 2.0, VR ready, DirectX® 12 Ultimate |
| NVIDIA® GeForce RTX™ 4050 Laptop GPU | Discrete | 6GB GDDR6 | 2370 MHz | 105W | DLSS 3.5, Dynamic Boost 2.0, DirectX® 12 Ultimate |
| NVIDIA® GeForce RTX™ 4060 Laptop GPU | Discrete | 8GB GDDR6 | 2370 MHz | 105W | DLSS 3.5, Dynamic Boost 2.0, VR ready, DirectX® 12 Ultimate |
| NVIDIA® GeForce RTX™ 4070 Laptop GPU | Discrete | 8GB GDDR6 | 2175 MHz | 115W | DLSS 3.5, Dynamic Boost 2.0, VR ready, DirectX® 12 Ultimate |

Notes:

[1] The actual TGP may depend on system configuration. System configured with 170W power adapter, TGP will be 105W. System configured with 230W power adapter, TGP will be 115W.

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI®, USB-C®)

- HDMI[®] supports up to 4K@60Hz
- \bullet USB-C $^{\!\!\rm e}$ supports up to 4K@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 32GB DDR5-4800

Memory Slots

Two DDR5 SO-DIMM slots, dual-channel capable

Memory Type

DDR5-4800

LOQ 15ARP9

Notes:

[1] Maximum memory is only to test technical readiness of notebook. Available memory to sell would vary.

Storage

Storage Support^[1]

Up to two drives, 2x M.2 SSD • M.2 2242 SSD up to 1TB each

Storage Slot

Two M.2 2280 PCIe® 4.0 x4 slots

Storage Type

| Disk Type | Interface | Offering | |
|--------------|--|-------------|--|
| M.2 2242 SSD | PCIe [®] NVMe [®] , PCIe [®] 4.0 x4 | 512GB / 1TB | |

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, optimized with Nahimic Audio

Microphone

Dual-microphone array

Camera**

- FHD 1080p, with E-shutter, fixed focus
- HD 720p, with E-shutter, fixed focus

Battery

Battery

60Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)

Max Battery Life^[1]

MobileMark® 25: 3.8 hr Local video (1080p) playback@150nits: 4.0 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark[®] 2014, MobileMark[®] 2018, MobileMark[®] 25, MobileMark[®] 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 170W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 230W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

Special Features

Special Features

LOQ 15ARP9

Lenovo

AI Chip: LA1

DESIGN

Display

Display

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features |
|-------|--------------------|-------|------|------------|----------------|-----------------|-------------------|----------------|-----------------|-------------------------------|--|
| 15.6″ | FHD (1920x1080) | None | IPS | 300nits | Anti- glare | 16:9 | 1000:1 | 100% sRGB | 144Hz | 85° / 85° / 85° / 85° | NVIDIA® G- SYNC®, TÜV Low Blue Light (Software) |

Touchscreen

Non-touch

Input Device

Pen

No support

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight**

- 4-Zone RGB backlight
- White backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)^[1]

359.86 x 258.7 x 21.9-23.9 mm (14.17 x 10.19 x 0.86-0.94 inches)

Weight^[2]

Starting at 2.38 kg (5.25 lbs)

Case Color

Luna grey

Surface Treatment

Painting

Case Material PC-ABS (top), PC-ABS (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo[®] lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®[1][2]

Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 card

WWAN

No support Ethernet^[3] Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

Notes:

[1] Bluetooth[®] may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Intel $^{\circ}$ Wi-Fi $^{\circ}$ 6 full features might be limited by country-level restrictions.

[3] Wake-on-LAN needs the power adapter plugged in.

Ports

Standard Ports^[1]

- 3x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-C[®] (USB 10Gbps / USB 3.2 Gen 2), with Lenovo[®] PD 140W and DisplayPort[™] 1.4^[2]
- 1x HDMI[®] 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Power connector

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

[2] PD 140W is the input power and requires the use of Lenovo® unique adapter, otherwise it may support lower than 140W.

Docking

Docking

Various docking solutions supported via USB-C[®]. For more compatible docking solutions, please visit <u>Docking for LOQ™ 15ARP9</u>

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

No fingerprint reader

BIOS Security

- Administrator password
- Master hard disk password
- Power-on password
- User hard disk password
- User password
- Self-healing BIOS
- More BIOS security features, please visit <u>BIOS Simulator</u>^[1]

Other Security

E-shutter

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)

Lenovo

- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories^[1]

- Lenovo[®] LOQ[™] M100 RGB Mouse (USB connector)
- None

Notes:

[1] For more compatible accessory solutions, please visit <u>Accessories for LOQ™ 15ARP9</u>.

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
- Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications⁽¹⁾

Green Certifications

- ErP Lot 3
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.

Other Certifications

Other Certifications

TÜV Rheinland[®] Low Blue Light (Software Solution)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without LOQ 15ARP9 March 31 2025

LOQ 15ARP9

notice.





AMD





